

PROJECT: _____
 CATALOG #: _____
 FIXTURE TYPE: _____
 NOTES: _____

TZ Industrial Strip Gen 1



PERFORMANCE INFORMATION

SERIES NUMBER	WATT	LUMENS	CCT
TZ 4 54 G1 4K	40W	5,348	4000K
TZ 4 54 G1 5K	40W	5,450	5000K
TZ 4 111 G1 4K	80W	10,891	4000K
TZ 4 111 G1 5K	80W	11,100	5000K

The *TZ Industrial Strip Gen 1* is easy to install and versatile for warehouses, supermarkets, and fabrication areas. This luminaire can be mounted together to create a row of linear illumination. For applications where precise control is required, lights optics can be placed to direct the light to its desired location.

APPLICATIONS

Commercial, Industrial, and Retail, etc.

REPLACEMENT

3 Lamp T8 32W and 4 Lamp T8 32W

OPTIONS



HBP-112-L7-OEM



BRI819P-B-D



EL UNV-10W

ORDERING GUIDE							EXAMPLE: TZ 4 54 G1 5K
Luminaire Type	Size	Lumen Output	Generation	Voltage	CCT	Finish	Options
TZ Industrial Strip	4= 4 ft	54 5,450 Lumens 111 11,100 Lumens	G1	BLANK= 120-277V	4K 4000K 5K 5000K	BLANK= White	BLANK= No Option HBP-112-L7-OEM= High/Low-Bay PIR On/Off Sensor BRI819P-B-D= PIR Motion/Photo Sensor, 120/277V AC, 1-10V Dimming (Choose one) L1= 360° Lens (Max. 25ft mounting height) L2= 360° Lens (Max. 40ft mounting height) EL UNV-10W= Emergency Backup Controller

Due to continuous product improvements, specification and/or equipment updates may change without notice.

SPECIFICATIONS

HOUSING

Body consists of fabricated 22ga steel

AMBIENT TEMPERATURE

Suitable for use in -40°C to 40°C (-40°F to 104°F)

MOUNTING

Surface mounting, Pendant mounting, T-bar mounting and Chain hanging

EFFICACY

Up to 139 lumens per watt (see individual wattage data)

CCT AND CRI

4000K, and 5000K CCT available; 80 CRI

OPTICS

General distribution acrylic Lens

WARRANTY

10-year limited warranty. Comprehensive warranty terms can be located on www.slgus.com.

ELECTRICAL

Standard 120/277V with 50/60Hz. Standard driver dimming 0-10V.

ENERGY DATA

Power factor above 90%.


FINISH

White Polyester Powder coat, 88% reflective painted after fabrication.

CERTIFICATIONS

UL Listed for damp and dry locations. FCC compliant. RoHs compliant. Design Lights Consortium® (DLC) Premium 5.0 qualified product. Not all versions of this product may be DLC qualified. Please visit www.slgus.com to confirm which versions are qualified.

DIMENSIONS



Due to continuous product improvements, specification and/or equipment updates may change without notice.

OPTIONS



HBP-112-L7-OEM

High/Low-Bay PIR On/Off Sensor

The **HBP-112-L7-OEM** on/off PIR motion sensor ideal for warehouses, distribution centers, gymnasiums, and other indoor applications.

Operation Voltage	Mounting Height	Coverage	Shape	Adjustable Time Delay	Operating Temperature	Applications
120V/ 277V/ 347V	15-40 ft	2.5x Height*	Cone	5/10/15/20/30 min. Default 15 min.	0°C to 70°C 32°F to 158°F	Indoor Only

* Covers a 100 ft diameter when the mounting height is 40 ft.



BRI819-P-B-D

Motion Sensor, 1-10V Dimming

The **BRI819-P-B-D** provides multi-level occupancy control with 1-10V adjustable dimming. This motion sensor can be attached externally to the fixture. Requires L1 or L2 lens depending on the mounting height.


Operation Voltage	Shape	Adjustable Time Delay	Operation Temperature	Mounting Height for L1	Mounting Height for L2
120/277V	Cone	10 sec - 60 min (adjustable)	-40°F to 167°F (-40°C to 75°C)	Max 25ft*	Max 40ft**

* Covers a 30 ft diameter when the mounting height is 25 ft.

** Covers a 60 ft diameter when the mounting height is 40 ft.

Due to continuous product improvements, specification and/or equipment updates may change without notice.

PHOTOMETRIC



TZ 4 54 G1 4K

ELECTRICAL LOAD

Series Number	Wattage	Current (A)			
		120V	208V	240V	277V
TZ 4 54 G1 4K	40W	0.33	0.19	0.17	0.14
TZ 4 54 G1 5K	40W	0.33	0.19	0.17	0.14
TZ 4 111 G1 4K	80W	0.67	0.38	0.33	0.29
TZ 4 111 G1 5K	80W	0.67	0.38	0.33	0.29

Due to continuous product improvements, specification and/or equipment updates may change without notice.